

AURA 7000 Thermal Receipt Printer



AURA 7000 Thermal Receipt Printer Series

The new AURA 7000 thermal receipt printer by POSIFLEX offers the performance, innovation, and affordability that you have come to expect. The high-resolution thermal print head provides quiet operation and the ability to print detailed graphics and bar codes for use in various applications.

The AURA clamshell design allows for easy drop-in paper replacement with auto-feed functionality. Settings include partial or full auto-cut capability and can control two cash drawers. An integrated image registration function (2MB of flash memory) allows for downloading and storing special character patterns and graphic logos.

Optional features includes a wall mount bracket, selection of 24-dot or 16-dot font modes and support of extended print modes.

For more information call (888) 968-1668 today!



www.posiflexusa.com

AURA 7000 Features:

- 180 mm/sec high-speed printer with 2MB flash memory
- Guillotine type auto-cutter
- Clam-shell, drop and load design for easy paper loading and print head cleaning
- Light weight, quiet and compact
- Supports bar code printing international character sets and other languages.
- Microsoft® WEPOS Certified (Windows Embedded for Point-of-Service)

Posiflex
30689 Huntwood Avenue
Hayward, CA 94544
Toll-free: 888.968.1668
Phone: 510.429.7097
Fax: 510.475.0982
E-mail: sales@posiflexusa.com

AURA Thermal Receipt Printer Leaders in POS Terminal Technology

PP7000 Specifications			
Model	PP7000S-104	PP7000C-104	PP7000U-104
Interface	RS232	Parallel	USB
Printing Method	Thermal sensitive line dot method		
Printing Speed	180 mm/sec		
Maximum Printable Width	72 mm (for 576 dots/line)		
Default Printing Width	64 mm (for 512 dots/line)		
Weight	1.35 Kg net (3lbs)		
Color	Black		
Operation Conditions	0°C ~ +40°C, 20%RH ~ 85%RH, non-condensing 35% above the auto cutter		
Storage Conditions	20°C ~ +60°C, 5%RH ~ 90%RH, non-condensing (paper excluded)		
Dimension: Machine Net (W x D x H)	148 mm (5.8") x 199 mm (7.8") x 144 mm (5.7")		
Dimension: Package (W x D x H)	221 mm (8.7") x 234 mm (9.2") x 256 mm (10.1")		
Safety	CE/FCC class A		
Option	Wallmount kit		
Printer Paper Specifications			
Paper Loading	Drop and Load, Clamp mechanism		
Paper Type	Thermal Roll Paper		
Paper Width	80 (or 58) + 0 / -1 mm		
Paper Roll Information	External side in heat-sensitive side		
Paper Roll Outer Diameter	83 mm max		
Paper Roll Inner Diameter	12 + 1 / -0 mm		
Paper Feed Method	Friction auto-feed		
Auto-Cutter Capability	500,000 cuts minimum		
Auto-Cutter Type	Guillotine		



About Posiflex

Established in 1984, Posiflex is recognized as a leading provider of innovative Point-of-Service (POS) hardware and platform technology used in diverse markets. Posiflex partners with applications software developers to provide reliable POS terminal systems to the hospitality, healthcare, medical, retail and specialized markets. The Company's products are sold through industry specialists, value-added resellers and distributors. All products are designed and manufactured in Taipei, Taiwan in two ISO 9001/9002/14001 certified laboratories and factories. Posiflex USA is located just north of the Silicon Valley, in Hayward, California. For additional information on Posiflex and the diverse product line, visit www.posiflexusa.com or call 888.968.1668.

POSIFLEX™
Leaders in POS Terminal Technology

30689 Huntwood Avenue
Hayward, CA 94544
Toll-free: 888.968.1668
Phone: 510.429.7097
Fax: 510.475.0982
e-mail: sales@posiflexusa.com